

INS-6010kV 10kV DIGITAL INSULATION TESTER

tinsley
PRECISION INSTRUMENTS

OVERVIEW

The digital insulation tester model INS-6010kV is Tinsleys' cutting edge insulation analyzer equipment and it is one of the most complete and sophisticated available in the international market. A powerful software allows for further analysis of tests results, including features such as graphical representation and automatic report generation. Its proven technology provides safe, reliable and accurate measurements of insulation resistances up to $10T\Omega$, with 4 pre-selected test voltages, 500V - 1kV - 5kV - 10kV. Other test voltages may be selected in steps of 25V, 100V or 500V.

A state-of-the-art microprocessor controls the equipment operation and enables the incorporation of advanced features which make measurements easier: auto-range selection, 4000 readings memory, AC/DC voltmeter, automatic measurement of Absorption Index and Polarization Index, leakage current and capacitance measurement, timer enabling programming of test duration, configurable Pass-Fail test, Step voltage test, real time clock and calendar.

Built-in chronometer, indicating elapsed time, in minutes and seconds, since the test started, up to 90 minutes.

Measured values are transmitted through the USB interface and are printed in the built-in printer as a registration of the performed test. Furthermore, the measured values are stored in a non-volatile internal memory. Up to 4000 measurements may be stored, to be transferred afterward to a computer running the MegaLogg2 program. This software allows a further analysis of the test results, including a graphical representation and automatic report generation. The real time clock and calendar, and the sequential test number, facilitates the identification of each test, and the organization of a predictive maintenance system by trend analysis.

The INS-6010kV is powered using a rechargeable battery and has an automatic charger that may be connected to 100 - 240V mains supply. The cabinet is strong and lightweight, easy to carry, impact-resistant and suitable to be used under severe weather conditions. Thus the megohmmeter supplies very reliable and accurate measurements both in laboratory



KEY FEATURES

- ➔ Microprocessor controlled
- ➔ Insulation resistances up to $10T\Omega$
- ➔ Auto-range
- ➔ Digital & bargraph reading
- ➔ Automated tests:
 - absorption index
 - polarization index
 - capacitance
 - leakage current
 - ac/dc voltmeter
- ➔ Chronometer up to 90 minutes
- ➔ Switchable filter to remove external noise interference
- ➔ Step voltage test
- ➔ Real time clock and calendar
- ➔ Built-in printer
- ➔ 4000 readings memory
- ➔ USB interface
- ➔ Software for data management
- ➔ Rechargeable battery

CONTACT US

1 Warner Drive
Springwood Industrial Estate
Braintree, Essex
CM7 2YW

Tel: 01376 335271
E-mail: info@tinsley.co.uk



www.tinsley.co.uk

SPECIFICATIONS

TEST VOLTAGES	500V - 1kV - 5kV - 10kV directly, one button selectable. 500V to 10kV in 25V, 100V or 500V steps. DC, negative.	BUILT-IN PRINTER	Prints elapsed time, actual voltage and resistance measured each 15 seconds
MAXIMUM RESISTANCE READING	10TΩ @ 10kV.	DATA OUTPUT	USB
DC VOLTMETER	15V up to 600Vdc. Accuracy: ±(5% of reading + 3 digits).	BUILT-IN CHRONOMETER	Shows elapsed time in mm:ss format. Count starts automatically for each measurement.
AC VOLTMETER	15V up to 600V r.m.s. Accuracy: ±(5% of reading + 3 digits).	MEGALOGG2 SOFTWARE	Friendly, easy to use software. Tests are represented in graphic and tabular views. With automatic report generator, including the operator's commentaries.
OVERVOLTAGE CATEGORY	CAT. III - 600V.	ENVIRONMENTAL PROTECTION	IP54 (with closed lid)
LEAKAGE CURRENT MEASUREMENT	1nA up to 1500μA ±(10% of reading + 3 digits).	SAFETY CLASS	In accordance with IEC 61010-1.
CAPACITANCE MEASUREMENT	50nF up to 10μF @ 500V. 50nF up to 5μF @ 1,000V. 30nF up to 2μF @ 2,500V. 30nF up to 1μF @ 5,000V. 30nF up to 680nF @ 10,000V. Accuracy: ±10% of reading ± 3 digits.	E.M.C.	In accordance with IEC 61326-1
SHORT CIRCUIT CURRENT	Max. 2mA.	ELECTRO MAGNETIC IRRADIATION IMMUNITY	In accordance with IEC 61000-4-3.
TEST VOLTAGES ACCURACY	± 3% of nominal test voltages on 10GΩ.	ELECTROSTATIC IMMUNITY	In accordance with IEC 61000-4-2.
MEGOHMMETER BASIC ACCURACY	± 5% of reading from 1MΩ to 1TΩ @ 10kV. ± 20% of reading from 1TΩ to 10TΩ @ 10kV. (for lower test voltages, the upper limit will be reduced proportionally). ± 20% of reading ± 5 digits from 10kΩ to 100kΩ. ± 10% of reading ± 5 digits from 100kΩ to 1MΩ.	POWER SUPPLY	Internal rechargeable battery 12,8V - 6Ah.
ADVANCED FEATURES	Automated Polarization Index calculation Automated Dielectric Absorption Ratio calculation Programmable Pass-Fail test Step Voltage Test 4000 readings memory Switchable filter to remove external noise interference	BATTERY CHARGER	AC adapter 18V - 2A. (Input 90 - 260V~ 45-65Hz).
		OPERATING TEMPERATURE RANGE	-5°C to 50°C.
		STORAGE TEMPERATURE RANGE	-25°C to 65°C.
		HUMIDITY RANGE	95% RH (non condensing).
		EQUIPMENT WEIGHT	Approx. 6.3kg.
		DIMENSIONS	406 x 330 x 174mm.
		INCLUDED ACCESSORIES	2 Measuring test leads 1 GUARD test lead 1 AC adapter 1 USB cable 1 Protective bag 1 User guide 1 MegaLogg2 software

All information provided by Tinsley in this datasheet is believed to be accurate. Tinsley reserves the right to discontinue and change specifications and prices at any time without prior notice. For further details, please refer to our website www.tinsley.co.uk